

# Belzona 1818 Protects Shaft from Abrasion

ID: 9114

Industry: *Cement*Customer Location: *Ireland*Application: *SHM-Solids Handling Machinery*Application Date: *February 2022*Substrate: *Carbon steel*Products: *Belzona 1818*

## Problem

*A separator shaft in a Cement Plant Raw Mill was suffering from severe fine particle abrasion from iron ore, shale and limestone at temperatures up to 100degC. The plant was on an unscheduled shutdown and needed the repair carried out quickly so that the mill could be out back into service*

Area prepared using a power  
tool (MBX Bristle Blaster)

Belzona 1818 applied

Belzona 1818 applied

Belzona 1818 after 15 months  
in service

## Application Situation

The repair needed to be completed quickly. The rapid cure time of Belzona 1818 enabled the Mill to be put back into service in a matter of hours.

## Application Method

The areas where Belzona 1818 was to be applied were prepared using an MBX Bristle Blaster.

## Belzona Facts

The customer had previously used welding and/or replacement of the shaft at a very high cost, taking many days to complete. Belzona 1818 allowed small repairs to be carried out quickly, with rapid cure and short back in service time.

For more examples of Belzona Know - How In Action, please visit <https://khia.belzona.com>

ISO 9001:2015

FS 695214

ISO 14001:2015

EMS 695213

Belzona products are

manufactured under an ISO

9000 Registered Quality

Management System.

[www.belzona.com](http://www.belzona.com)